

Indiana University – Purdue University Fort Wayne
Opus: Research & Creativity at IPFW

Computer and Electrical Engineering Technology &
Information Systems and Technology Senior Design
Projects

School of Engineering, Technology and Computer
Science Design Projects

12-6-1986

Design and Development of an Programmable Power Supply

Mike Boschet

Indiana University - Purdue University Fort Wayne

Follow this and additional works at: http://opus.ipfw.edu/etcs_seniorproj



Part of the [Computer Sciences Commons](#), and the [Engineering Commons](#)

Opus Citation

Mike Boschet (1986). Design and Development of an Programmable Power Supply.
http://opus.ipfw.edu/etcs_seniorproj/148

This Senior Design Project is brought to you for free and open access by the School of Engineering, Technology and Computer Science Design Projects at Opus: Research & Creativity at IPFW. It has been accepted for inclusion in Computer and Electrical Engineering Technology & Information Systems and Technology Senior Design Projects by an authorized administrator of Opus: Research & Creativity at IPFW. For more information, please contact admin@lib.ipfw.edu.

TECHNICAL REPORT OF THE DESIGN AND
DEVELOPMENT OF ~~AN~~ PROGRAMMABLE POWER SUPPLY

FOR
Professors ~~s~~ Emery
Electrical Engineering Technology Department
Purdue University
Fort Wayne, Indiana

BY
Mike Boschet
Fred King

DECEMBER 6, 1986

**ABSTRACT
OF
PROGRESS REPORT FOR THE DESIGN OF
PROGRAMMABLE POWER SUPPLY**

BY

Mike Boschet

This report presents the results of Senior Design Phase I and Phase II. The subject of this report is the design and construction of a Programmable Power Supply. The Programmable Power Supply is divided into two modules, the Controller, and The Power Supply. The use of modular construction give flexibility to the design of the system. Each module can be designed by separate engineers, there by reducing development time and design effort.

The Power Supply (designed by Mike Boschet) utilizes off-the-shelf parts. The reference voltage for the voltage regulators is supplied by an D-to-A converter. The use of the D-to-A converter allows the regulators to be programmed using a digital output from an external controller.

The Power Supply Controller (designed by Fred King) is designed around a microcomputer. The microprocessor is used to reduce cost, power consumption, and construction time. The Controller communicates with the Power Supply by sending 8-bit words through an external bus. The Controller reads input from the operator through the keyboard and calculates the proper bit pattern to be sent over the buss to the Power Supply.

The report details operation of the Power Supply and Controller. Benefits of the design and problems incurred with the design are also noted in the report.

TABLE OF CONTENTS

TABLE OF FIGURES.....	i
INTRODUCTION	
PURPOSE.....	1
STATEMENT OF THE PROBLEM.....	2
PLAN OF PROCEDURE.....	2
POWER SUPPLY	
OVER VIEW.....	3
MAIN POWER CIRCUIT.....	3
PROGRAMMABLE VOLTAGE REGULATORS.....	5
CONTROLLER	
OVER VIEW.....	13
MICROPROCESSOR CIRCUIT.....	13
KEYBOARD DISPLAY INTERFACE CIRCUIT.....	16
POWER SUPPLY INTERFACE CIRCUIT.....	16
SOFTWARE	
OVER VIEW.....	19
INTERRUPT ROUTINES.....	19
COMMAND ROUTINES.....	20
CONCLUSION	
BENEFITS.....	21
CONSIDERATIONS.....	21
GLOSSARY.....	22
REFERENCES.....	23
APPENDIX A (PROPOSAL).....	24
APPENDIX B (POWER SUPPLY PARTS LIST).....	33
APPENDIX C (CONTROLLER PARTS LIST).....	34
APPENDIX D (SOFTWARE LISTING).....	35

TABLE OF FIGURES

FIGURE

1 MAIN POWER.....	4
2 DATA INPUT.....	6
3 POSITIVE D-TO-A CONVERTER.....	7
4 ADJUSTABLE POSITIVE REGULATOR.....	9
5 NEGATIVE D-TO-A CONVERTER.....	11
6 ADJUSTABLE NEGATIVE REGULATOR.....	12
7 MICROPROCESSOR CIRCUIT.....	15
8 KEYBOARD DISPLAY INTERFACE CIRCUIT.....	17
9 POWER SUPPLY INTERFACE CIRCUIT.....	18